For service, contact the store where you purchased the device.

USER MANUAL

UV-C Blue Sterilizer



Rev. A/03/2026

Thank you for choosing our product.

Please read the user manual before first use and keep it for future reference

The UV-C Blue Sterilizer is a device for dry disinfection, i.e., without the use of chemical solutions. During operation, it uses UV-C radiation with a wavelength of 254 nm, which destroys vegetative forms of microorganisms.

Technical Specifications	
Voltage	220-240V 50Hz
Power	8W

Device dimensions



Application

1. The UV sterilizer is used to disinfect tools made of metal, plastic, wood, and composite materials (scissors, combs, tweezers, etc.).
2. Disinfection is performed using UV rays, ensuring that the equipment is not exposed to mechanical damage. UV sterilization involves exposing the material to ultraviolet radiation.
3. This radiation alters the structure of nucleic acids, which is why it is most effective against vegetative forms of microorganisms.
4. The device is ideal for use in beauty salons, spas, aesthetic medicine clinics, and hair salons.

Instructions for use

1. Place the device on a stable surface, lift the blue flap of the sterilizer, insert the instruments inside, and close the flap.

   Note: Instruments placed in the sterilizer should be clean, dry, and pre-washed. Instruments should not overlap.
2. Plug the sterilizer into an electrical outlet. Turn on the device using the on/off switch located on the back of the unit.
3. The device will start operating; the sterilization time is approximately 30–45 minutes.
4. After the desired time has elapsed, turn off the device using the on/off switch.

5. Open the sterilizer and remove the items (this is not mandatory—you can also leave them in the container).
6. The instruments are ready for use.

Note

Once the disinfection cycle is complete, turn off the device using the on/off button. If the power cord is damaged or if any other malfunctions occur, contact an authorized service center to avoid any risk.

Recommendations

1. Make sure you have placed the device on a flat, stable surface to reduce the risk of it falling and becoming damaged.

1. Never leave the device plugged in and unattended.
2. Use the device as intended, as described in the manual.
3. Never use this device if the power cord or plug is damaged.
4. Do not use the device if it is not working properly or if it has been dropped, damaged, or submerged in water.
5. Do not pull directly on the cord to remove the plug from the outlet.
6. This product is for indoor use only. Do not expose it to direct weather conditions.
7. Clean the device periodically to prevent dirt buildup. It is best to clean the device with a damp cloth.
8. Do not wrap the power cord around the device.

Safety Precautions

1. This device is professional equipment intended for use in beauty salons. Operation of the device exclusively by qualified beauty professionals helps prevent adverse effects during treatment.

2. Do not disassemble the device or attempt to use it for purposes other than those specified in this user manual. All maintenance and repairs must be performed exclusively by an authorized service technician.

3. Do not install or operate the device near liquids, in wet areas, or with wet hands. Ensure that no liquids enter the device.

4. Immediately unplug the device and contact the authorized service in the following cases: a) liquid has entered the device, b) the device emits a strange odor, smoke, or makes unusual noises, c) the power cord has been damaged, d) the device has been knocked over or its casing has been damaged.

5. Do not place any objects on the cables. Do not install the device in areas where someone might step on the power cord.
6. For safety reasons, unplug the power cord from the outlet after each use of the device.
7. Do not place foreign objects inside the device. If a foreign object gets inside, unplug the power cord from the outlet and contact the distributor or manufacturer.
8. Do not place the device on an unstable cart, shelf, or vehicle. The device may be damaged if it falls.
9. To ensure the device’s specified service life, it is recommended to wait one

minute before pressing the power button again (between turning it on and off, and vice versa).

10. The power supply must comply with the specifications listed on the nameplate. Otherwise, there is a risk of the device malfunctioning, being damaged, or even catching fire.

CAUTION

1. In the event of damage to the power cord or other malfunctions, contact an authorized service center—this will help prevent hazards.
2. This device may be used by children aged 8 years and older, by persons by individuals with reduced physical or mental capabilities, as well as by those unfamiliar with the operation of this equipment, provided they are given appropriate supervision or instruction on how to use it safely and understand the associated risks.
3. Do not leave the device unattended when children or persons without sufficient knowledge of how to use the device are in the vicinity.
4. The device is not intended for use by children. Do not allow children to play with the device.
5. This electrical device is not a toy. Improper use of or contact with the can pose a risk of injury or death; therefore, the device must be used and stored out of the reach of children.

Disposal of the device



To protect the environment, in accordance with Directive 2012/19/EU on waste electrical and electronic equipment, used electrical equipment must be collected separately and taken to collection points for waste electrical and electronic equipment. Follow the guidelines for disposing of this type of equipment and do not dispose of it in household waste bins. At the end of their useful life, these devices still contain valuable recyclable components; therefore, they should be sent for recycling to appropriate collection points.

Storage and Transport

The device should be transported at temperatures ranging from (–)20°C to (+)40°C exclusively in its original packaging. It should be stored in a well-ventilated room with relative humidity not exceeding 90%. Operating temperature range: (+)10°C to (+)40°C. During processes
During storage and transport, do not throw or drop the device, or expose it to mechanical shocks or weather conditions.